



Polyester Resin Type Insulator



Model No.	SR2-12
Rated Voltage(kV)	12
Creepage Distance(mm)	420
Impulse Withstand Voltage(kV)	75
Dry Power Frequency Withstand Voltage(kV)	48
Wet Power Frequency Withstand Voltage(kV)	35
Tensile Strength(kN)	6
Weight(kg)	1.2



Model No.	SR3-36
Rated Voltage(kV)	36
Creepage Distance(mm)	137
Impulse Withstand Voltage(kV)	250
Dry Power Frequency Withstand Voltage(kV)	125
Wet Power Frequency Withstand Voltage(kV)	115
Tensile Strength(kN)	6
Weight(kg)	5.6



Model No.	SR4-12
Rated Voltage (kV)	12
Power Frequency Withstand Voltage(kV)	45
Creepage Distance (mm)	340
Weight (kg)	2
Dimension (mm)	100*170



Model No.	SR5-12
Rated Voltage (kV)	12
Power Frequency Withstand Voltage(kV)	45
Creepage Distance (mm)	430
Weight (kg)	1.2
Dimension (mm)	100*208



Model No.	ZJ1-10Q
Rated Voltage (kV)	12
Power Frequency Withstand Voltage(kV)	45
Creepage Distance (mm)	260
Weight (kg)	0.7
Dimension (mm)	65*140



Polyester Resin Type Insulator



Model.No.	EL-3M
End Diameters (A/B)(mm)	70
Height (H)(mm)	60
Leakage Distance(mm)	88
Rated Voltage(kV)	3.6
Low Frequency Dielectric Strength(kV)	16
Impulse Voltage Resistance(kV)	60
Persistent Bending Strength, 1Min(kg)	400
Tensile Strength(kg)	> 1200
Torque Strength(kg-m)	> 25



Model.No.	EL-6M
End Diameters (A/B)(mm)	70
Height (H)(mm)	90
Leakage Distance(mm)	125
Rated Voltage(kV)	7.2
Low Frequency Dielectric Strength(kV)	22
Impulse Voltage Resistance(kV)	75
Persistent Bending Strength, 1Min(kg)	400
Tensile Strength(kg)	>1200
Torque Strength(kg-m)	> 25



Model.No.	EL-15
End Diameters (A/B)(mm)	70
Height (H)(mm)	142
Leakage Distance(mm)	210
Rated Voltage(kV)	15
Low Frequency Dielectric Strength(kV)	50
Impulse Voltage Resistance(kV)	110
Persistent Bending Strength, 1Min(kg)	400
Tensile Strength(kg)	>1500
Torque Strength(kg-m)	>25



Model.No.	EL-24
End Diameters (A/B)(mm)	70
Height (H)(mm)	210
Leakage Distance(mm)	356
Rated Voltage(kV)	24
Low Frequency Dielectric Strength(kV)	60
Impulse Voltage Resistance(kV)	125
Persistent Bending Strength, 1Min(kg)	300
Tensile Strength(kg)	>1500
Torque Strength(kg-m)	>25



Model No.	CG5/10Q
Rated Voltage (kV)	12
Power Frequency Withstand Voltage.(kV)	45
Creepage Distance (mm)	300
Weight (kg)	1.2
Dimension (mm)	95*140



Epoxy Resin Type Insulator & Bushing



Epoxy Resin Wall Bushing

Model No.	TG3-10Q
Rated Voltage (kV)	12
Power Frequency Withstand Voltage(kV)	46
Creepage Distance (mm)	380
Weight (kg)	2.46
Dimension (mm)	110*180



Epoxy Resin Wall Bushing

Model No.	TG3-35Q
Rated Voltage (kV)	35
Power Frequency Withstand Voltage(kV)	85
Creepage Distance (mm)	1000
Weight (kg)	15
Dimension (mm)	260*260



Epoxy Resin Contact Box

Model No.	CH3-10Q/250
Rated Voltage (kV)	12
Power Frequency Withstand Voltage(kV)	85
Creepage Distance (mm)	430
Weight (kg)	5
Dimension (mm)	130*200



Epoxy Resin Contact Box

Model No.	CH3-10Q/150
Rated Voltage (kV)	12
Power Frequency Withstand Voltage(kV)	45
Creepage Distance (mm)	320
Weight (kg)	2.46
Dimension (mm)	85*280



Epoxy Resin Sensor/Sensor Insulator

Model No.	CG5-35Q
Rated Voltage (kV)	35
Power Frequency Withstand Voltage(kV)	85
Creepage Distance (mm)	830
Weight (kg)	5-6.8
Dimension (mm)	145*350